



Technical datasheet No.: **1150.2**  
**Product:** POLYMAR® POLYFOAM 1,5  
**Article No.:** 7865 5241

<b>Type of coating and finish</b>		
Type of coating	<b>PVC, PVC-foam</b>	
for type of coating	<b>thickness of the foam, 1,5 mm</b>	
Flame retardancy	<b>DIN 4102: B1</b>	
Total weight	<b>960</b> g/m <sup>2</sup>	DIN 53352, EN ISO 2286-2
Tensile strength (warp/weft)	<b>2800 / 2700</b> N/50 mm	DIN 53354, DIN EN ISO 1421/V1
Tear strength (1) (warp/weft)	<b>320 / 280</b> N	DIN 53363
Adhesion (1)	<b>15</b> N/cm	LB 3.04-1 (Complan)
Cold resistance	<b>- 10</b> °C	DIN 53361
High Temperature	<b>+ 70</b> °C	Directive Complan
Light fastness	<b>&gt;6</b> Note, Val. DIN 54004, DIN EN ISO 105 B02	
<b>Base fabric</b>		
Material	<b>PES</b>	DIN ISO 2076
Yarn count	<b>1100</b> dtex	DIN ISO 2060

These indicated technical data are based on average results. Due to production procedures slight deviations can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.